

# Product Selection Guide

New products are frequently introduced. Please visit [www.DeltaPSU.com](http://www.DeltaPSU.com) for latest product updates.

Product Type	Series	Model Name	Phase			PFC	Output Voltage	Output Current	Output Power	Input Voltage Range*
			1	2	3					
DIN Rail Power Supply	CliQ II <ul style="list-style-type: none"> <li>IP20 connector</li> <li>Power Boost up to 5s</li> </ul>	DRP024V060W1B□	●				24 V	2.5 A	60 W	85-264 V <sub>AC</sub> (DC input range 120-375 V <sub>DC</sub> )
		DRP024V120W1B□	●					5.0 A	120 W	
		DRP024V240W1B□	●					10.0 A	240 W	
		DRP024V480W1B□	●				●	20.0 A	480 W	
		DRP024V060W1N□	●					2.5 A	60 W	85-264 V <sub>AC</sub> (DC input range 120-375 V <sub>DC</sub> )
		DRP-24V100W1NN	●				●	3.8 A	91.2 W	
		DRP-24V120W2BN	●	●				5.0 A	120 W	2 × 180-550 V <sub>AC</sub> or 180-305 V <sub>AC</sub> (Single Phase) (DC input range 254-780 V <sub>DC</sub> )
		DRP-24V240W2BN	●	●			●	10.0 A	240 W	
		DRP024V060W3B□		●	●			2.5 A	60 W	3 × 320-600 V <sub>AC</sub> or 2 × 360-600 V <sub>AC</sub> (DC input range 450-800 V <sub>DC</sub> )
		DRP024V120W3B□		●	●			5.0 A	120 W	
		DRP024V240W3B□		●	●			10.0 A	240 W	For 960W: 3 × 320-600 V <sub>AC</sub> or 2 × 380-600 V <sub>AC</sub> (DC input range 450-800 V <sub>DC</sub> )
		DRP024V480W3B□		●	●	●		20.0 A	480 W	
		DRP024V960W3BN		●	●	●		40.0 A	960 W	
		DRP048V060W1B□		●				48 V	1.25 A	60 W
	DRP048V120W1B□		●			●		2.5 A	120 W	
	DRP048V240W1B□		●			●		5.0 A	240 W	
	DRP048V480W1B□		●			●		10.0 A	480 W	
	CliQ III <ul style="list-style-type: none"> <li>Slim design with high power density</li> <li>Power Boost up to 5s</li> </ul>	DRP-24V120W1CAN	●			●	24 V	5.0 A	120 W	88-264 V <sub>AC</sub>
		DRP-24V120W1CBN	●			●		5.0 A	120 W	88-264 V <sub>AC</sub> (DC input range 88-375 V <sub>DC</sub> )
		DRP-24V240W1CAN	●			●		10.0 A	240 W	88-264 V <sub>AC</sub>
		DRP-24V240W1CBN	●			●		10.0 A	240 W	88-264 V <sub>AC</sub> (DC input range 88-375 V <sub>DC</sub> )
		DRP-24V480W1CAN	●			●		20.0 A	480 W	88-264 V <sub>AC</sub>
		DRP-24V480W1CBN	●			●		20.0 A	480 W	88-264 V <sub>AC</sub> (DC input range 88-375 V <sub>DC</sub> )
	CliQ M <ul style="list-style-type: none"> <li>Slim design with high power density</li> <li>Advanced Power Boost</li> <li>Maritime approvals</li> </ul>	DRM-24V80W1PN	●			●	24 V	3.4 A	81.6 W	85-276 V <sub>AC</sub> (DC input range 88-375 V <sub>DC</sub> )
		DRM-24V120W1PN	●			●		5.0 A	120 W	85-264 V <sub>AC</sub> (DC input range 88-375 V <sub>DC</sub> )
		DRM-24V240W1PN	●			●		10.0 A	240 W	85-276 V <sub>AC</sub> (DC input range 88-375 V <sub>DC</sub> )
		DRM-24V480W1PN	●			●		20.0 A	480 W	
		DRM-24V960W1PN	●			●		40.0 A	960 W	85-264 V <sub>AC</sub>
DRM-24V480W3PN			●	●	●		20.0 A	480 W	3 × 320-600 V <sub>AC</sub> or 2 × 380-600 V <sub>AC</sub>	
DRM-24V960W3PN			●	●	●		40.0 A	960 W		
DRM-24V480W1SN		●			●		20.0 A	480 W	85-276 V <sub>AC</sub> (DC input range 88-375 V <sub>DC</sub> )	

\* DC input is certified for selected models

## Model Numbering

DR	P	XXXV	XXXW	□	□	□	
DIN Rail	Product Type P - Power Supply	Output Voltage	Output Power	Phase Input 1 - Single Phase 2 - Two Phase 3 - Three Phase	B - CliQ II Series N - NEC Class 2	A - Metal case, with Class I, Div 2 and ATEX approvals N - Metal case, without Class I, Div 2 and ATEX approvals Y - Plastic case, with Class I, Div 2 and ATEX approvals Z - Plastic case, without Class I, Div 2 and ATEX approvals	
DR	P -	XXV	XXXW	1	C	□	N
DIN Rail	Product Type P - Power Supply	Output Voltage	Output Power	Phase Input 1 - Single Phase	C - CliQ III Series	Input Voltage A - AC Input B - AC & DC Input	N - Metal case, without Class I, Div 2 and ATEX approvals
DR	M -	XXV	XXXW	□	□	□	
DIN Rail	Product Series M - CliQ M Series	Output Voltage	Output Power	Phase Input 1 - Single Phase 3 - Three Phase	P - Advanced Power Boost (APB) S - SIL 3	N - Metal case, without Class I, Div 2 and ATEX approvals	
DR	V -	XXV	XXXW	1	P	□	N
DIN Rail	Product Series V - CliQ VA Series	Output Voltage	Output Power	Phase Input 1 - Single Phase	P - Advanced Power Boost (APB)	N - Metal case, without Class I, Div 2 and ATEX approvals	

# Product Selection Guide

New products are frequently introduced. Please visit [www.DeltaPSU.com](http://www.DeltaPSU.com) for latest product updates.

Product Type	Series	Model Name	Phase			PFC	Output Voltage	Output Current	Output Power	Input Voltage Range*	
			1	2	3						
DIN Rail Power Supply	CliQ VA	DRV-24V120W1PN	●			●	24 V	5.0 A	120 W	85-264 V <sub>AC</sub> (DC input range 88-375 V <sub>DC</sub> )	
		DRV-24V240W1PN	●			●		10.0 A	240 W		
		DRV-24V480W1PN	●			●		20.0 A	480 W		
	Force-GT	NEW	DRF-12V120W1GBA	●			●	12 V	10.0 A	120 W	90-264 V <sub>AC</sub>
			DRF-12V240W1GBA	●			●		20.0 A	240 W	
			DRF-24V120W1GBA	●			●	24 V	5.0 A	120 W	
		DRF-24V240W1GBA	●			●		10.0 A	240 W	90-264 V <sub>AC</sub>	
		DRF-24V480W1GBA	●			●		20.0 A	480 W		
		DRF-48V120W1GBA	●			●	48 V	2.5 A	120 W		
		DRF-48V240W1GBA	●			●		5.0 A	240 W	90-264 V <sub>AC</sub>	
		DRF-48V480W1GBA	●			●		10.0 A	480 W		
		DRF-24V120W3GBA		●	●		24 V	5.0 A	120 W		3 x 320-575 V <sub>AC</sub> (3-Phase) or 2 x 340-575 V <sub>AC</sub> (2-Phase) (DC input range 450-800 V <sub>DC</sub> )
		DRF-24V240W3GBA		●	●			10.0 A	240 W		
		DRF-24V480W3GBA		●	●	●		20.0 A	480 W		
	DRF-24V960W3GBA		●	●	●		40.0 A	960 W			
	LYTE	DRL-12V75W1AZ	●				12 V	6.25 A	75 W	85-264 V <sub>AC</sub>	
			●				24 V	3.125 A	75 W	85-264 V <sub>AC</sub>	
			●				48 V	1.57 A	75.36 W	85-264 V <sub>AC</sub>	
	LYTE II	DRL-12V120W1EN□	●				12 V	10.0 A	120 W	90-264 V <sub>AC</sub>	
			●			●		20.0 A	240 W		
		DRL-24V120W1EN□	●				24 V	5.0 A	120 W	90-264 V <sub>AC</sub>	
			●			●		10.0 A	240 W		
		DRL-24V480W1EN□	●			●		20.0 A	480 W	90-264 V <sub>AC</sub>	
		DRL-48V120W1EN□	●				48 V	2.5 A	120 W		
DRL-48V240W1EN□		●			●		5.0 A	240 W			
DRL-48V480W1EN□	●			●		10.0 A	480 W				

\* DC input is certified for selected models

## Model Numbering

DR	F -	XXV	XXXW	□	G	B	A
DIN Rail	Product Series F - Force-GT Series	Output Voltage	Output Power	Phase Input 1 - Single Phase 3 - Three Phase	G - General Type	B - Screw Terminal	A - Delta Standard

DR	L -	XXV	XXXW	1	A	□
DIN Rail	Product Type L - LYTE Family	Output Voltage	Output Power	Phase Input 1 - Single Phase	A - LYTE Series with Standard Bracket	A - Metal case without DC OK Relay Contact S - Metal case with DC OK Relay Contact Z - Plastic case without DC OK Relay Contact

DR	L -	XXV	XXXW	1	E	N	□
DIN Rail	Product Type L - LYTE Family	Output Voltage	Output Power	Phase Input 1 - Single Phase	E - LYTE II Series with Slim Design	N - No DC OK Relay Contact	Blank - No coating A - With coating

DR	F -	XXV	XXXW	□	G	B	A
DIN Rail	Product Series F - Force-GT Series	Output Voltage	Output Power	Phase Input 1 - Single Phase 3 - Three Phase	P - General Type	B - Screw Terminal	A - Delta Standard

# Product Selection Guide

New products are frequently introduced. Please visit [www.DeltaPSU.com](http://www.DeltaPSU.com) for latest product updates.

Product Type	Series	Model Name	Phase	PFC	Output Voltage	Output Current	Output Power	Input Voltage Range*	
			1						
DIN Rail Power Supply	CHROME <ul style="list-style-type: none"> <li>• Compact</li> <li>• Class II double isolation</li> <li>• NEC Class 2</li> </ul>	DRC-5V10W1A□	●		5 V	1.5 A	7.5 W	90-264 V <sub>AC</sub>	
		DRC-12V10W1A□	●		12 V	0.83 A	10 W	90-264 V <sub>AC</sub>	
		DRC-12V30W1A□	●			2.1 A	25.2 W		
		DRC-12V60W1A□	●			4.5 A	54 W		
		DRC-12V60W1CZ	●			4.5 A	54 W	90-264 V <sub>AC</sub> (DC input range 125-375 V <sub>DC</sub> )	
		DRC-12V100W1AZ	●			6.0 A	72 W	90-264 V <sub>AC</sub>	
		DRC-24V10W1A□	●			24 V	0.42 A	10 W	90-264 V <sub>AC</sub>
		DRC-24V10W1HZ	●				0.42 A	10 W	
		DRC-24V30W1A□	●				1.25 A	30 W	
		DRC-24V60W1A□	●				2.5 A	60 W	
	DRC-24V100W1A□	●				3.8 A	91.2 W	90-264 V <sub>AC</sub> (DC input range 125-375 V <sub>DC</sub> )	
	SYNC <ul style="list-style-type: none"> <li>• Compact</li> <li>• NEC Class 2</li> <li>• Competitively priced</li> </ul>	DRS-5V30W1NZ	●		5 V	3.0 A	15 W	85-264 V <sub>AC</sub> (DC input range 120-375 V <sub>DC</sub> )	
		DRS-5V50W1A□	●			6.0 A	30 W		
		DRS-5V50W1N□	●			5.0 A	25 W		
		DRS-12V50W1N□	●		12 V	4.0 A	48 W	85-264 V <sub>AC</sub>	
		DRS-24V30W1AZ	●		24 V	1.25 A	30 W	85-264 V <sub>AC</sub> (DC input range 120-375 V <sub>DC</sub> )	
		DRS-24V30W1NZ	●			1.25 A	30 W		
		DRS-24V50W1N□	●			2.1 A	50 W		
		DRS-24V100W1A□	●	●		4.0 A	96 W		
		DRS-24V100W1N□	●	●		3.8 A	91.2 W		

\* DC input is certified for selected models

## Model Numbering

DR	C -	XXV	XXXW	1	□	□
DIN Rail	Product Type C - Isolation Class II Power Supply	Output Voltage	Output Power	Phase Input 1 - Single Phase	A - No PFC C - AC & DC Input, No PFC H - Household Approval	Z - Black plastic case G - Grey plastic case C - Black plastic case, with conformal coating <sup>1)</sup>

1) Options for DRC-12V60W1A□, DRC-24V60W1A□ and DRC-24V100W1A□ only

DR	S -	XXV	XXXW	1	□	□
DIN Rail	Product Series S - Sync Series	Output Voltage	Output Power	Phase Input 1 - Single Phase	A - Non NEC Class 2 N - NEC Class 2	Z - Without DC OK Relay Contact R - With DC OK Relay Contact